



	10" FLG.	12" FLG.	14" FLG.
OPENING	10.00	12.00	14.00
BOLT CIRCLE	14.25	17.00	18.75
FLANGE O.D.	16.20	19.00	21.00
NR TAPPED HOLES	12	12	12
SIZE HOLES	7/8 - 9	7/8 - 9	1 - 8
TAP DEPTH	1.31	1.31	1.50

W - INLET
 W' - DISCHARGE
 AD - SNEAVE WIDTH
 AE - SNEAVE DIAMETER

RCS-J WHISPAIR BLOWER - BOTT. DRIVE

ALL DIMENSIONS IN INCHES

FRAME SIZE	A	B	C	D	E	F	G	H	J	K	M	N	O	P	R	U	V	KEYWAY	W	W'	AA	AD	AE	OIL CAPACITY		APPROX. WEIGHT	
																								G.E.	D.E.		
817 JV	13.75	24.25	38.63	13.00	4.63	10.75	1.00	1.00	4.00	3.25	14.50	5.00	30.00	25.50	17.00	2.75	4.00	.625 x .313	10" FLG	10" FLG	12.75	7.19	13.2	144 FL. OZ.	80 FL. OZ.	1620 LBS	
821 JV	"	27.88	42.25	"	"	12.56	"	"	"	"	16.31	"	"	"	"	"	"	"	"	12" FLG	10" FLG	"	"	"	"	"	1800 LBS
826 JV	"	33.13	47.50	"	"	15.19	"	"	"	"	18.94	"	"	"	"	"	"	"	"	12" FLG	12" FLG	"	"	"	"	"	2075 LBS
832 JV	"	38.50	52.00	"	"	17.88	"	"	"	"	21.63	"	"	"	"	"	"	"	"	14" FLG	12" FLG	"	"	"	"	"	2325 LBS

CERTIFIED CORRECT FOR	V-BELT DRIVE DATA	
	CUSTOMER ORDER NO.	BELTS
	ROOTS ORDER NO.	DRIVE SHEAVE
	DATE	DRIVEN SHEAVE
		CENTER DISTANCE



DRESSER INDUSTRIES, INC.
 ROOTS OPERATIONS
 900 WEST MOUNT STREET, CONNERSVILLE, INDIANA 47331
 TELEPHONE: 317/825-2181

REM 10/25/05
 804448-1/10/05
 RBG-11/24/05

864-928-021

BY: RDR 9/19/96 166 PM 4876-6 CHKD: APP: RDA