





8 SLOTS-7/8 WIDE  
(USE 5/8 BOLTS W/WASHER)

W-INLET  
W'-DISCHARGE  
AD-SHAFT WIDTH  
AE-SHAFT DIA.  
ALL DIM. IN INCHES

	6" FLG
OPENING	6.00
BOLT CIRCLE	9.50
FLANGE O.D.	11.00
NO. TAPPED HOLES	8
SIZE HOLES	3/4-10
TAP DEPTH	1.15

UNIT SIZE	APPROX. OIL CAP. (IN FL. OZ.)				G.D.
	VERT.	HORIZ.			
	BEAR END	DRIVE END	BEAR END	DRIVE END	
6"	28.3	15.5	52.1	30.5	6.00

FRAME SIZE	A	B	C	D	E	E'	F	G	J	K	L	M	N	O	O'	P	R	U	V	KEYWAY	W	W'	AA	AB	AD	AE	AF	AG	AH	AJ	AK	AL	APPROX WEIGHT
65	11.00	10.00	18.38	8.75	1.00	4.00	3.81	.38	5.38	2.13	3.00	5.68	3.53	21.63	15.13	12.75	11.75	1.375	2.75	.312x.156	3"NPT	3"NPT	6.38	9.89	3.44	8.00	19.75	17.00	6.06	4.97	5.13	2.13	250 LBS
68	"	13.00	21.38	"	"	"	5.81	"	"	"	"	"	7.18	3.68	"	"	"	"	"	"	5"NPT	5"NPT	"	"	"	"	"	7.43	6.47	"	"	290 LBS	
615	"	20.00	28.38	"	"	"	8.81	"	"	"	"	"	10.68	"	"	16.25	15.00	"	"	"	6"FLG	6"FLG	7.50	"	"	"	"	10.93	9.97	"	"	430 LBS	

MFG. REF. 62753021

CONFIDENTIAL

THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION OF DRESSER ROOTS, DRESSER, INC. IT SHALL BE HELD IN STRICTEST CONFIDENCE, AND BE USED ONLY IN CONJUNCTION WITH DRESSER ROOTS BUSINESS.

- REF: EP58
- FLATNESS
  - ∠ ANGULARITY
  - ∥ PARALLELISM
  - ⊕ TRUE POSITION
  - STRAIGHTNESS
  - CONCENTRICITY
  - ⊥ PERPENDICULARITY
  - ⌒ PROFILE OF LINE
  - ⊙ PROFILE OF A SURFACE
  - ∅ DIAMETER
  - ✓ FINISH IN MICRO INCHES

A	ADDED SIGHT GLASS LOCATING DIMS.	RDG	2/9/04	T240	AGP	AGP
REVISIONS		BY	DATE	CHANGE NOTICE	CHKD.	APP

DO NOT SCALE FOR DIMENSIONS  
ALL DIMENSIONS SHOWN IN BRACKETS ( ) ARE MILLIMETERS

ORDER No.

DR. RK	08/15/03
CHKD. RK	08/15/03
APP. AGP	08/15/03
DOB	
SCALE NTS	
CAD FILE / DIRECTORY	

### DIMENSIONAL DRAWING 6" U-RAI DSL BLOWER



DIMENSIONAL TOLERANCES UNLESS OTHERWISE SPECIFIED  
FINISHED DIMENSIONS  
TWO PLACE DECIMALS (1.00) - 2.00  
THREE PLACE DECIMALS (1.000) - 2.000  
FOUR PLACE DECIMALS (1.0000) - 2.0000

Dresser ROOTS, Dresser, Inc.  
Houston, TX USA

T30381021

REV A